


— 1



Δ

POWER MAP





DY=Dummy parts
=not populated



SCD1U10V2KX-5GP
D1U = 0.1uF (2D2U means 2.2uF)
10Voltage (6D3V means 6.3V)
2 = size 0402, K tolerance
K=tolerance
[C code as below:]
G=2%
J=5%
K=10%
M=20%
X=temp characteristics
[C Series/Temp]
N=NPO
X=X7R/X5R
Y=Y5V
-5=different symbol/customer
GP= Green Part (RoHS)


562R2F- GP
562 = 562 ohm, (2K2R means 2.2K ohm)
2 = size 0402
F = 1% tolerance
GP= Green Part (RoHS)
RC size code as below:
1 = 0201
2= 0402
3= 0603
5= 0805
6= 1206
R tolerance code as below:
D=0.5%
F= 1%
J= 5%

FAN CONTROLLER

















Wiwynn
8F, 90, Sec. 1, Hsin Tai Wu Rd,
Hsichih, Taipei Hsien 221, Taiwan, R.O.C
HW RAD Dept. II

Title

Screws

Size
A3

Document Number
Honey_Badger_FCB

Rev
1

Date: Friday, January 30, 2015

Sheet 11 of 13

BLANK

BLANK

BLANK