


NOTES

- 1. INTERPRET DIMENSIONS PER ASME Y14.5M-2009.
- 2. ALL DIMENSIONS ARE MM.
- 3. THE MATERIALS AND MANUFACTURING METHODS USED MUST COMPLY WITH ROHS 2002/95/EC.
- 4. ALL DIMENSIONS SHOWN SHALL BE CONSIDERED CRITICAL TO FUNCTION AND CHECKED DURING FIRST ARTICLE INSPECTION.
- 5. COMPONENT SHALL BE CLEAN AND FREE FROM FOREIGN MATERIAL. DIRT,OIL,GREASE,OR OTHER CONTAMINANTS ARE NOT ALLOWED.
- 6. TOLERANCES UNLESS OTHERWISE SPECIFIED ARE:
 - HOLE TO HOLE: 0.13MM/.005IN
 - HOLE TO FOLD: 0.25MM/.01IN
 - EDGE TO FOLD: 0.25MM/.01IN
 - FOLD TO FOLD: 0.40MM/.016IN
 - HOLE TO EDGE: 0.25MM/.01IN
 - HOLE DIAMETER: 0.08/.003IN
 - ANGLES: 0.5
- 7. MATERIAL SHALL RESIST THE CREATION OF ZINC WHISKERS, SUCH AS ASTM A653 AND JIS G3302 SGOC. ELECTOGALVINIZED PLATING IS NOT ALLOWED.
- 8. ALL EDGES SHALL BE CONDITIONED FOR HANDLING WITH A BURR NO GREATER THAN 10% OF MATERIAL THICKNESS AND SHALL CONFORM TO UL SAFETY SPECIFICATION 1439.

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	1	INITIAL RELEASE		SM

	NAME	DATE	facebook		
DRAWN	MILLS	7MAR13			
CHECKED			TITLE: KIT, Bracket switch BRACKET, 1U SWITCH, OR2		
ENG APPR.					
MFG APPR.					
PROPRIETARY AND CONFIDENTIAL					
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FACEBOOK. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FACEBOOK IS PROHIBITED.			SIZE	DWG. NO.	REV
			B	27-000404	1
			SHEET 1 OF 2		



SIZE	DWG. NO.	REV
B	27-000404	1
SHEET 2 OF 2		