



OPEN

Compute Project

Project Olympus Chassis Mechanical Specification

Author:

Larry Cannon, Senior Mechanical Engineer, Microsoft

Revision History

Date	Description
03/01/2017	Version 0.7
11/01/2017	Version 1.0 Release to OCP



© 2017 Microsoft Corporation.

As of November 1, 2017, the following persons or entities have made this Specification available under the Open Web Foundation Final Specification Agreement (OWFa 1.0), which is available at <http://www.openwebfoundation.org/legal/the-owf-1-0-agreements/owfa-1-0>

Microsoft Corporation.

You can review the signed copies of the Open Web Foundation Agreement Version 1.0 for this Specification at <http://www.opencompute.org/participate/legal-documents/>, which may also include additional parties to those listed above.

Your use of this Specification may be subject to other third party rights. THIS SPECIFICATION IS PROVIDED "AS IS." The contributors expressly disclaim any warranties (express, implied, or otherwise), including implied warranties of merchantability, non-infringement, fitness for a particular purpose, or title, related to the Specification. The entire risk as to implementing or otherwise using the Specification is assumed by the Specification implementer and user. IN NO EVENT WILL ANY PARTY BE LIABLE TO ANY OTHER PARTY FOR LOST PROFITS OR ANY FORM OF INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER FROM ANY CAUSES OF ACTION OF ANY KIND WITH RESPECT TO THIS SPECIFICATION OR ITS GOVERNING AGREEMENT, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), OR OTHERWISE, AND WHETHER OR NOT THE OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

CONTRIBUTORS AND LICENSORS OF THIS SPECIFICATION MAY HAVE MENTIONED CERTAIN TECHNOLOGIES THAT ARE MERELY REFERENCED WITHIN THIS SPECIFICATION AND NOT LICENSED UNDER THE OWF CLA OR OWFa. THE FOLLOWING IS A LIST OF MERELY REFERENCED TECHNOLOGY: INTELLIGENT PLATFORM MANAGEMENT INTERFACE (IPMI); I²C IS A TRADEMARK AND TECHNOLOGY OF NXP SEMICONDUCTORS ; EPYC IS A TRADEMARK AND TECHNOLOGY OF ADVANCED MICRO DEVICES INC.; ASPEED AST 2400/2500 FAMILY PROCESSORS IS A TECHNOLOGY OF ASPEED TECHNOLOGY INC.; MOLEX NANOPITCH, NANO PICOBLADE, AND MINI-FIT JR AND ASSOCIATED CONNECTORS ARE TRADEMARKS AND TECHNOLOGIES OF MOLEX LLC; WINBOND IS A TRADEMARK OF WINBOND ELECTRONICS CORPORATION; NVLINK IS A TECHNOLOGY OF NVIDIA; INTEL XEON SCALABLE PROCESSORS, INTEL QUICKASSIST TECHNOLOGY, INTEL HYPER-THREADING TECHNOLOGY, ENHANCED INTEL SPEEDSTEP TECHNOLOGY, INTEL VIRTUALIZATION TECHNOLOGY, INTEL SERVER PLATFORM SERVICES, INTEL MANAGABILITY ENGINE, AND INTEL TRUSTED EXECUTION TECHNOLOGY ARE TRADEMARKS AND TECHNOLOGIES OF INTEL CORPORATION; SITARA ARM CORTEX-A9 PROCESSOR IS A TRADEMARK AND TECHNOLOGY OF TEXAS INSTRUMENTS; GUIDE PINS FROM PENCOM; BATTERIES FROM PANASONIC. IMPLEMENTATION OF THESE TECHNOLOGIES MAY BE SUBJECT TO THEIR OWN LEGAL TERMS.

Contents

1	Introduction to the Project Olympus Chassis System.....	6
2	Chassis Specification by Component.....	9
2.1	Rack.....	9
2.2	Tracks	11
2.3	Power and Management Distribution Unit (PMDU)	12
2.4	Server Tray and Power Supply.....	16
2.5	Project Olympus Air Blocker	22
2.6	Project Olympus Component Interfaces.....	24
2.6.1	Tracks to Rack	24
2.6.2	PMDU in Tracks.....	27
2.6.3	Server Tray/PSU into Rack	30

List of Figures

Figure 1.	Project Olympus Chassis System.....	7
Figure 2.	Rear View Showing Components Assembled (note that VAC cables from the data center enter the rack top at the rear, then connect to the two large connectors on the PMDU).....	8
Figure 3.	Rack Dimensions	9
Figure 4.	Right Side View - EIA Rail Spacing	10
Figure 5.	EIA Rail Mounting Hole Spacing.....	11
Figure 6.	Project Olympus Tracks.....	11
Figure 7.	PMDU Front Face	13
Figure 8.	PMDU 3-Phase Input Connectors	14
Figure 9.	Cone Screw for Mounting PMDU to Tracks	15
Figure 10.	Cone Screws on Left Side of PMDU	15
Figure 11.	Bottom Mounting Bracket (top bracket identical).....	16
Figure 12.	Project Olympus Server Tray and Power Supply Unit (tray top cover removed for clarity)	17
Figure 13.	Rear Mounting of the PSU in the Tray (note guide sleeve and power input connector)	18
Figure 14.	Front Mounting of the PSU in the Tray	18
Figure 15.	Tray General Dimensions.....	19
Figure 16.	PSU Dimensions	20
Figure 17.	Close-up View of Pins and Latch	21
Figure 18.	Right Iso View Showing Mounting Pins.....	21
Figure 19.	Iso View of Air Blockers in Rack	22
Figure 20.	Air Blocker Views Showing Both Sides	23
Figure 21.	Rear Iso Showing Air Blockers Installed	24
Figure 22.	Track/Front EIA Rail Interface	25

Figure 23. Track/Middle EIA Rail Interface	26
Figure 24. Track/Rear EIA Rail Interface	26
Figure 25. Cone Screws on PMDU Prior to Insertion in Track.....	27
Figure 26. Cone Screws Seated in Keyhole Slots.....	28
Figure 27. PMDU Top and Bottom Rack Brackets.....	29
Figure 28. Tray Insertion Detail.....	30
Figure 29. Tray and PSU Mating with PMDU, Left Side View	31
Figure 30. Tray Latch Engagement.....	32
Figure 31. Blue Release Tab	33

Project Olympus System Chassis Specification List

Table 1 lists the Project Olympus system chassis specifications pertaining to the chassis.

Table 1: List of Specifications and Drawings

Specification title	Description
Project Olympus Rack Specification	Describes the mechanical rack hardware used in the system
Project Olympus Server Tray Specification	Describes the sheet metal tray used in the system
Project Olympus PSU Specification	Describes the custom Power Supply Unit (PSU) used in the server
Project Olympus Power and Management Distribution Unit (PMDU) Specification	Describes the Power Management Distribution Unit (PMDU)
Project Olympus Track Drawing	Describes the tracks that mount in the system rack.

This document is intended for designers and engineers who will be building chassis for Project Olympus systems.

1 Introduction to the Project Olympus Chassis System

The Project Olympus chassis system is a modular design to provide more flexibility in enabling servers and other components. Modules are designed to a simple envelope of 1U increments with blind-mate A/C power and management connection. Cooling and D/C power conversion is performed inside each module to enable rapid development without worry of interaction with other modules in the rack. This modularity also provides for costs to be paid only for the components employed. The Project Olympus chassis is comprised of the rack, 1U 'tracks', one and two U server trays with power supplies in them, and a Power and Management Distribution Unit (PMDU) that allow the system to be configured – mixed and matched – according to need. See Figures 1 and 2.

The general scheme is that the tracks are mounted to the EIA rails in the rack, the PMDU hangs on slots in the tracks at the left rear of the rack and is then secured with brackets at its top and bottom, and the server trays (one and/or two U) slide into the tracks and are stopped at the rear when the power supplies in the trays connect with the PMDU. The PMDU thus serves as a mechanical stop to the trays as well as supplying power to them. At U locations where a network switch or other device that has its own EIA rail mounting brackets is planned, the tracks are omitted.

This specification addresses primarily the general mechanical attributes of the system components. Detailed mechanical and electrical descriptions of the Project Olympus components can be found in their respective specifications.




Figure 1. Project Olympus Chassis System




Figure 2. Rear View Showing Components Assembled (note that VAC cables from the data center enter the rack top at the rear, then connect to the two large connectors on the PMDU)

2 Chassis Specification by Component

2.1 Rack

Project Olympus encompasses both 42U or 48U racks that are 1200mm deep. The rack dimensions are shown in Figure 3.




Figure 3. Rack Dimensions

The racks are built per EIA-310-D and UL 2416 standards. The distances between the front, mid, and back rails are shown in Figure 4. Figure 5 shows EIA rail mounting hole spacing across the front of the rack.




Figure 4. Right Side View - EIA Rail Spacing




Figure 5. EIA Rail Mounting Hole Spacing

2.2 Tracks

The main feature of the Project Olympus mounting system is a 1U tall sheet metal piece called a track. It fits into the front, mid, and rear EIA rails with two bayonet features at each location, as shown in Figure 6. The tracks are installed in pairs, one for the left side and one for the right side, the same part for each side.




Figure 6. Project Olympus Tracks

Track Features:



1. Rear Rail Interface
2. Front Rail Interface
3. Middle Rail Interface
4. Blade Interface
5. Keyhole slots for PMDU mounting

2.3 Power and Management Distribution Unit (PMDU)

The PMDU is a sheet metal enclosure that mounts to the Project Olympus tracks without the use of tools, and provides front-facing, blind-mate connectors having both power and signal contacts for each U location in the rack. Once mounted in the tracks, brackets at the top and bottom of the PMDU tie it to the rack with screws. When Project Olympus trays are inserted in the rack, they mate up with the PMDU via guide pin sleeves and the hot-plug, blind-mate connectors. There are guide pins mounted on the front face of the PMDU, located just above each connector. The pins pre-mate with the guide sleeves on the rear faces of the Project Olympus PSUs in the trays, providing initial guidance for the blind-mate connectors. Figure 8 shows the connectors and guide pins.




Figure 7. PMDU Front Face

The PMDU has both 42U and 48U configurations, and has two standardized input bulkhead-mount connectors, Figure 9, for VAC Feed A and VAC Feed B. The standardized input connector is a 7-pin connector comprised of earth ground and 3 phase-pairs rated at 250VAC per pair. The standardized connectors are both 4 wire and 5 wire facility cable assemblies having the desired voltage and amperage rating. The PMDU takes both the VAC Feed A and VAC Feed B through facility cables, and distributes the 6 phase-pairs (2 feeds X 3 phase-pairs/feed) to each U location in the system. The facility VAC cables enter the rack through access holes at the top rear of the rack cover, and when mated with the PMDU, are locked in place with built-in levers.

The PMDU also monitors and reports the voltage, current, and power for each of the 6 phase-pairs. The PMDU shall be able report values to the management system via the I²C communications port.

The standardized connector-to-facility cables comes in three options: 5 Wire 415VAC 30A/32A, 4 Wire 208VAC 50A, and 4 Wire 208VAC 30A.




Figure 8. PMDU 3-Phase Input Connectors

Figures 10, 11, and 12 show the mechanical features of the PMDU that allow it to connect to the tracks and the rack. These interfaces will be covered later in the specification.




Figure 9. Cone Screw for Mounting PMDU to Tracks




Figure 10. Cone Screws on Left Side of PMDU




Figure 11. Bottom Mounting Bracket (top bracket identical)

2.4 Server Tray and Power Supply

The Project Olympus server tray is a full-width sheet metal assembly. Because the server tray connects to and draws power from the Project Olympus PMDU via the Project Olympus power supply unit (PSU) mounted in it, the server tray and PSU are considered an integral unit, seen in Figure 13. The Project Olympus power supply is also a sheet metal enclosure, having output a power output connector on the front and an input connector at the rear.

The rear of the PSU – the input end – fits into a rectangular opening at the left rear of the tray. The front of the PSU is secured to the tray with two washers and screws. Both the rear and front mountings are loose, allowing the PSU to float slightly and absorb tolerance variations in the system assembly. The guide sleeve at the rear of the PSU aligns it with the PMDU when the server tray is inserted in the rack.




Figure 12. Project Olympus Server Tray and Power Supply Unit (tray top cover removed for clarity)

Mounting at the rear of the tray is shown in Figure 14, and front end mounting is shown in Figure 15. A flange at the rear of the tray captures the rear of the PSU.




Figure 13. Rear Mounting of the PSU in the Tray (note guide sleeve and power input connector)




Figure 14. Front Mounting of the PSU in the Tray

The overall dimensions of the Project Olympus tray are shown in Figure 16, and the dimensions of the Project Olympus PSU are shown in Figure 16.




Figure 15. Tray General Dimensions




Figure 16. PSU Dimensions

Each tray has six pairs of headed metal pins installed in the sheet metal on its left and right side. See Figures 18 and 19 for details. When the tray is inserted into a rack with tracks, the pins ride on the bearing surfaces of the tracks and support the tray.




Figure 17. Close-up View of Pins and Latch




Figure 18. Right Iso View Showing Mounting Pins

2.5 Project Olympus Air Blocker

The Project Olympus air blocker is a flame-rated, injection molded part that prevents cold aisle air from entering the rack in unpopulated U locations. The blocker is designed to be reversible, so that it can be used in U locations that have tracks – such as the locations where tracks are required to support the PMDU, and in locations with no tracks. See Figures 19, 20, and 21.




Figure 19. Iso View of Air Blockers in Rack



Figure 20. Air Blocker Views Showing Both Sides




Figure 21. Rear Iso Showing Air Blockers Installed

2.6 Project Olympus Component Interfaces

2.6.1 Tracks to Rack

The tracks connect to the racks in three locations, the front, middle and rear EIA rails, as shown in Figures 22, 23, and 24. Though the tracks fit loosely, once installed, they are held in by built-in spring features. The loose fit accommodates dimensional variations in the rack while still providing secure mounting for rack components.




Figure 22. Track/Front EIA Rail Interface




Figure 23. Track/Middle EIA Rail Interface




Figure 24. Track/Rear EIA Rail Interface

2.6.2 PMDU in Tracks

The PMDU is installed without tools into the tracks by virtue of cone-shaped screws on the left side of the PMDU fitting into keyhole slots in four of the tracks (U location of tracks dependent on configuration of rack, i.e., 42U or 48U). Figure 25 shows the screws just before installation, and Figure 26 shows the screws seated in the slots. The angled cone surfaces of the screws pull the PMDU snug against the tracks, and the weight of the PMDU holds it down in the bottom of the keyholes.




Figure 25. Cone Screws on PMDU Prior to Insertion in Track




Figure 26. Cone Screws Seated in Keyhole Slots

Once the PMDU is seated in the tracks, it is fastened to the rack via a bracket and two screws at the bottom and a bracket and two screws at the top. The two brackets connect to cross pieces in the rack. See Figure 27. This secures the PMDU during transport, and prevents rotational movement during server tray installation.




Figure 27. PMDU Top and Bottom Rack Brackets

2.6.3 Server Tray/PSU into Rack

When a Project Olympus server tray is inserted in a rack, chamfered surfaces on the tracks guide the tray mounting pins onto the bearing surfaces of the tracks. See Figure 28.




Figure 28. Tray Insertion Detail

As the tray is moved further into the rack and the PSU in the rear of the tray approaches the PMDU, the guide pin sleeve on the rear of the PSU begins to engage with the guide pin on the front of the PMDU. This can be seen in Figure 29.




Figure 29. Tray and PSU Mating with PMDU, Left Side View

The tray stops forward travel when the face of the guide pin sleeve touches the front face of the PMDU. In this position, the connectors are unmated 0.5mm. Even with all tolerances taken into account, there is still 2.5mm of contact engagement at 4.5σ . If there is any misalignment between the guide pin sleeve and the guide pin as they begin to engage, the floating capability of the rear of the PSU in the tray will accommodate this.

At the same time that the tray is stopping its forward travel due to the PMDU, the side latches at the front of the tray engage with the back surfaces of the front EIA rails, preventing the tray from disconnecting. Chamfered leading edges on the latches allow them to be pushed out of the way as the tray is pushed in. Built-in spring action pops them back out for engagement with the EIA rails. See Figure 30.




Figure 30. Tray Latch Engagement

The tray can be removed from the system by pulling out on the blue tabs on either side of the tray. The left tab is shown in Figure 31.




Figure 31. Blue Release Tab