

OPEN
Compute Project

Agema AG6248C-PoE Switch
Specifications
Revision .02

Agema Systems Inc.

Fremont CA

Table of Contents

1.	<i>Revision History</i>	3
2.	<i>Licenses</i>	4
3.	<i>Scope</i>	5
4.	<i>Hardware Functionality</i>	6
4.1.	Block Diagram	6
4.2.	Physical Dimensions	7
4.3.	CPU Subsystem	8
	CPU- BCM56340 (ARM Cortex A9 processor).....	8
4.3.1.1.	AG6248C-POE PoE+ Daughter Board	9
4.3.2.	LED Definition for System	11
4.3.2.1.	LED Definition for System	11
4.3.2.2.	Port LED definition	12
4.3.3.	Power Supply & Fan Tray allocation.....	13
4.3.3.1.	AC Power Supply	14
4.3.3.2.	PSU LED Handle definition	14
4.4.	Fan specification	15
4.5.	Mechanicals	16
4.6.	Faceplate layout and artwork	17
4.7.	PCB Stack up	18
5.	<i>Software Support</i>	19
6.	<i>Critical Components</i>	19
7.	<i>Technical Specs and Environmental Requirements</i>	21

1. Revision History

Rev	Date	Description	Page	Editor
0.0	07/27/2015	Initial draft		Roger.Chao
0.01	03/04/2016	Add Licenses section and describe optional second PSU	4 & 10	Bob Lee
0.02	04/06/2016	1.Add POE port power allocation table and noted.	10	Roger.Chao
		2.Add DC-DC converter part number.	19	
		3.Add the POE daughter board overview.	20	

2. Licenses

This license is based on Open Computer Project Hardware license (Permissive) version 1.0 (“OCP Permissive License”). If you do not agree the terms and conditions of this license, please do not use, copy, modify, distribute or otherwise utilize this specification. As a recipient of this specification, you are granted (1) the right to use, reproduce, publicly display, and publicly perform this specification which is considered an Improvement under OCP Permissive License, and to modify and prepare derivative works of it, under the copyright owned or controllable by us; and (2) to make, have made, use, offer to sell, sell, import, and otherwise transfer a networking product implementing this specification, under all of our Necessary Claims. If you bring an action (including a cross-claim or counterclaim in a lawsuit) against us or any other recipient of this specification alleging that any product implementing this specification or the use of it directly or contributory infringes any patent, then any licenses granted herein (including copyright and patent licenses) will terminate as of the date such action is brought. For the purpose of this license, the said Improvement does not include an extension or addition of functionality of a Specification, that there is a commercially feasible means of manufacturing it as a separate physical component. Our grant of this license does not prevent any third party from asserting or alleging any infringement of intellectual properties in connection of your implementation or exploitation of this specification. In case of any alleged infringement of any intellectual property, you agree to defend, indemnify and hold harmless us from and against any suits, actions, proceedings, losses, damages, costs, expenses, liabilities and penalties resulting from or arising out of your implementation or exploitation of this specification. This specification is provided “as is”, without any warranties, either express or implied, including, without limitation, non-infringement, merchantability, or fitness for a particular purpose. You are solely responsible for determining the appropriateness of using this specification and assume any risks associated with your exercise of permissions under this license. In no event and under no legal theory, whether in tort, contract, or otherwise, we shall be liable to you for any damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this license or out of the use or inability to use this specification (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if we are advised of the possibility of such damages. All capital words not defined herein shall have the same definitions with OCP Permissive License. The OCP Permissive License supplements this license and the terms and conditions hereunder together with the OCP Permissive License constitute the entire agreement with regard to this license.

As of March 31, 2016, the following persons or entities have made this Specification available under the Open Web Foundation Final Specification Agreement (OWFa 1.0), which is available at <http://www.openwebfoundation.org/legal/the-owf-1-0-agreements/owfa-1-0>:

Agema Systems, Inc.

3. Scope

This document defines the technical specification for the Agema AG6248C-PoE switch submitted to the Open Compute Project Agema Open Platform Switch

Overview

The Agema are highly integrated for one rack unit system. And the **AG6248C-POE** platforms are all L3 management switch.

AG6248C-POE (POE model)	48x1G Cu ports including UPOE/POE+ function + 2x1G SFP combo ports + 2x 10G SFP+ ports
------------------------------------	--

For the AG6248C-POE, the system also including a serial port (RS232 interface) and OOB port for management functions.

Feature


- External Serial RS232 port (RJ45)
- Support one USB port (type-A) for system file access
- 48 1Gbps copper ports(RJ45)
- Two combo 1Gbps SFP fiber ports
- Two 10Gbps SFP+ fiber ports
- The Front panel Management copper port RJ45 (OOB) support 10M/100M/1G speeds
- 48x1G copper ports (RJ45) support PoE+ (IEEE802.3af/at)
- AG6248C-POE, port number 1-12 of RJ45 ports support UPoE capability
- Front panel LED display for system status, Fan, TEMP and power (PSUs) status
- Integrated Dual Core ARM Cortex A9 IC with large memory. 4GB NAND, 1GB/DDR3 SDRAM
- Temperature monitoring. (TMP75).
- For AG6248C-POE platforms, there is hot pluggable Fan tray. And Fans' speeds can be monitored and controlled by Fan controller.
- Standard 1U chassis high

AG6248C-POE series configuration table

Description	AG6248C-POE
PSU	1100W*1
MAC	BCM56340
PHY	BCM54282*5 BCM54285*1 BCM84752*1
PHY (OOB Port)	BCM54616s
POE controller	PD69100*1 PD69108ILQ*8


4. Hardware Functionality

4.1. Block Diagram




4.2. Physical Dimensions

440 x 387 x 44 mm (W x D x H)
17.32 x 15.24 x 1.73 inch



4.3. CPU Subsystem




CPU- BCM56340 (ARM Cortex A9 processor)

The BCM56340 device integrates a dual core ARM Cortex A9 processor running at 1 GHz to allow a completed solution to be developed without an external host processor.

4.3.1.1. AG6248C-POE PoE+ Daughter Board

AG6248C-POE PoE+ Block Diagram



POE Power manager

The Agema product PoE models that software needs to handle the power budget for POE+ ports turn on/off control. The Agema product is using the Microsemi controller can support for the Power budget control, Port Priority function and other PoE features.

1. **Power budget setting:** The power budget limitation for optional table.

Model Name	System Power Maximum Dissipation	PoE Power budget limited			
		One PSU support		Two PSUs support for Option	
		Maximum PSU output ability	POE+ power turn on limitation	Maximum PSUs output ability	POE+ power turn on limitation
AG6248C	140W	1100W	Power budget is 900W: The total POE supply power need to within the 900W.	2200W	Power budget is 1800W All PoE+/UPOE ports can be turned on.

Case	Qty	54V (w)	PoE Power budget	PoE Port qty	PoE port Allocation
1 PSU 1100w	1	900	900	48.00	30port x 30w (PoE+)
2 PSU 1100w	1	900	900	48.00	12port x 60w(UPoE) + 6port x 30w (PoE+)

2. **Port Priority setting:**
 - a. If the total power exceeds the power budget then low priority ports will turn off directly.
 - b. The Port Priority will be setting by user via software feature.
 - c. All of ports will have a low priority as default setting.

Note:

1. POE port power allocation is based on user requirement and able to up to 900W per PSU.
2. Port 1~ Port 12 can be able to UPoE with 60W per port.
3. Port 13 ~ Port 48 only be able to PoE+ with 30W per port.
4. AG6248C has optional for second PSU for future used if needed.


4.3.2.LED Definition for System

4.3.2.1. LED Definition for System

System LEDs indication including System, Master, Power, temperature and Fan Status

Feature	Detailed Description	Comment
STATUS LED (Bi-color LED)	Solid Green –Normal operation Blinking Green – Booting Solid Red –Critical system error Blinking Red –Non-critical system error (fan fail, power supply fail)	At front side
POWER 1 LED (Single color LED)	Off – Power failure or no power Solid Green – Power is good Blinking Green – locator function is enable	At front side
POWER 2 LED (Single color LED)	Off – Power failure or no power Solid Green – Power is good Blinking Green – locator function is enable	At front side
FAN LED (Bi-color LED)	Solid Green –fan powered and @expected rpm Solid Red –fan failed	At front side
TEMP LED (Bi-color LED)	Solid Green – System temperature is below threshold limit Solid Red –System temperature has exceeded threshold limit	At rear side

Note: The system temperature threshold is 75 centigrade when one of thermal sensors over temperature. And the TEMP LED will be lighted up to RED.



4.3.2.2. Port LED definition

1G copper port LEDs

Feature	Detailed Description	Comment
Link/SPD LED (Left bi-color LED)	Green – Link at 1000Mbps Yellow – Link at 10/100Mbps Solid – Link OFF – No Link	
PoE Switch POE/ACT LED (Right bi-color LED)	Green Blinking – Activity, PoE power OFF Yellow Blinking – Activity, PoE power ON Yellow Solid – No Activity, PoE power ON OFF –No Activity, PoE power OFF	

SFP Combo port LEDs

Feature	Detailed Description	Comment
Link/SPD LED (Left bi-color LED)	Off – No Link Solid green –Link on 1000Mbps speed Solid Amber –Link on 100Mbps speeds	
ACT LED (Right single color LED)	Off – No Activity Blinking green – Activity	

SFP+ port LEDs

Feature	Detailed Description	Comment
Link/SPD LED (Left bi-color LED)	Off – No Link Solid green –Link on 10G speed Solid Amber –Link on 1G speeds	
ACT LED (Right single color LED)	Off – No Activity Blinking green –Activity	

OOB Ethernet port LEDs

Feature	Detailed Description	Comment
Link/SPD LED (Left bi-color LED)	Off – No Link Solid green – Link on 1G speed Solid Amber – Link on 100M or 10M speeds	
ACT LED (Right single color LED)	Off – No Link Blinking green – Transmitting / Receiving	


Console port LEDs

Feature	Detailed Description	Comment
Link/SPD LED (Left bi-color LED)	Off – No Link Solid green – Link is present	


4.3.3. Power Supply & Fan Tray allocation

AG6248C-POE PoE system

- AG6248C-POE PSU: 1100W, DC output 54V/20.37A,
- 2 Fan units in one Fan tray (pluggable), Fan spec: 12000rpm 12VDC



4.3.3.1. AC Power Supply




4.3.3.2. PSU LED Handle definition

The PSU has a LED handle to indicate the power supply status. The LED indication is controlled by PSU internal MCU. And the LED definitions please refer to below description.


1100W PSU LED behaviors

- Off – No Power Supply
- Solid Green – Power is good
- Solid Red – detected, power bad



4.4. Fan specification

Description	Manufacturer	Part number
Air flow : Front to Back	Delta Electronics	FFB03812HN-DT26



NOTE:



- 1.LEAD WIRE UL1061 AWG#24
PIN 1.RED WIRE----(+)
PIN 2.BLUE WIRE----(F00)
PIN 3.BLACK WIRE----(-)
- 2.HOUSING: MOLEX 5051-03 22-01-1032
- 3.TERMINAL: MOLEX 2759T 08-50-0113
- 4.THIS PRODUCT IS ROHS COMPLIANT.

UNIT: MM(INCH)


4.5. Mechanicals

**Main board PCB dimension*

428.4*241.5*2.1*



4.6. Faceplate layout and artwork



The front panel views for main key Components of AG6248C-POE

- 48x 1G Copper ports (RJ45)
- 2x 1G fiber ports
- 2x 10G fiber ports
- 1x OOB port (RJ45)
- 1x Console port (RJ45)
- System LEDs (Status/Fan/PSU 1/PSU2/TEMP)
- 1x USB-Type-A



The rear panel views for main key components of AG6248C-POE

- 1x PSU (1100W, DC output 54V/20.37A),
- 1x Fan tray module



4.7. PCB Stack up

8-Layer

Structure (Stack up)			
Layer	Type		
	Solder mask		
1	TOP	L1 - SIGNAL (0.5oz)	
	prepreg		
2	G	L2 - GROUND(1oz)	
	core		
3	S	L3 - SIGNAL(1oz)	
	prepreg		
4	PWR	L4 - Power (1oz)	
	core		
5	PWR	L5 - Power (1oz)	
	prepreg		
6	S	L6 - SIGNAL(1oz)	
	core		
7	G	L7 - GROUND(1oz)	
	prepreg		
8	BOT	L8 - SIGNAL(0.5oz)	
	solder mask		
board thickness=2.1mm			

5. Software Support

AG6248C-POE supports ONIE

6. Critical Components

Description	Manufacturer	Part number
IC ETH SW 48P+4P 1GB+10GB	Broadcom	BCM56340A0KF SBG
IC ETH X'CEIVER 8P GB FBGA-400B	Broadcom	BCM54285C1KFBG
IC ETH X'CEIVER 8P GB FBGA-256B	Broadcom	BCM54282C1KFBG
IC ETH PHY 2P 10GB BGA-144B	Broadcom	BCM84752A1IFSBG
IC ETH X'CEIVER 10/100/GB-T FBGA-100B	Broadcom	BCM54616SC0KFBG
PHONE JACK LF LED 10P8C 6*2	Delta	RPGC-12AF0360DR
PHONE JACK LF LED 10P8C 6*2	Delta	RPGC-12AF8050DR
Dual core ARM Cortex-A9	Broadcom	BCM56340 Integrated CPU
DDR3 SDRAM	Samsung	K4B4G1646D0BCK0
NAND Flash	Micron	MT29F32G08ABAAAWP-Z:A
DC-DC Converter 36V 75V 12V 216W	Delta	Q48SK12018NRFH
Power Supply Unit (PSU)	Delta	DSP-1100CB-2 A
PoE	Microsemi	PD69100-026301 + PD69108ILQ
Fans	Delta	FFB03812HN-DT26
USB	Wieson	G3502-121141



7. Technical Specs and Environmental Requirements

Technical Specifications

Network Protocol and Standards Compatibility

IEEE802.3 CSMA/CD
IEEE802.3u 100BaseTx
IEEE802.3z 1000BaseSX
IEEE802.3z/ab 1000BaseT
IEEE802.3an 10GBase-T
IEEE802.3af/at
SFF-8341
SFF-8079
IEEE802.3x flow control

Interface

USB connector (USB to DB9)

Physical Dimensions

440 x 387 x 44 mm (W x D x H)
17.32 x 15.24 x 1.73 inch

Electromagnetic Emission

- FCC Class A, CE Class A, VCCI Class A

Safety Agency approval

- UL, CUL